

TT 34 and TC 49 – digital electronic timers and counters

Tecnologic's timers and counters are fully programmable whilst remaining easy to use. Used where accurate counting or timing of a critical process is needed (not real time) these powerful units cover a multitude of applications.



FEATURES

- 4 DIGIT DISPLAY
- HOURS, MINS, SECS, 10TH'S
- 2 VOLT FREE INPUTS
- 2 RELAY OUTPUTS
- FULLY PROGRAMMABLE
- IP65 FRONT FACIA

SPECIFICATION

- OUTPUTS: Up to 2 x relay (8 amp res)
- SUPPLY VOLTAGE: 12 AC/DC, 24 VAC/DC, 100-230 V
- INPUTS: 2 x digital inputs, for start, stop reset, hold
- DIMENSIONS: 33mm x 75mm x 64mm (TT34)
- 48mm x 48 mm x 95mm (TT49)
- APPROVALS: CE, UL, CSA, ROHS compliance

PART CODES

DESCRIPTION

PRICE (£)

1 - 9 10 +

PART CODES	DESCRIPTION	PRICE (£)	
		1 - 9	10 +
TT34-FCRR	75X33MM TIMER, 12 V SUPPLY, 2 X RELAY	POA	POA
TT34-HCRR	75X33MM TIMER, 100-230V, 2 X RELAY	POA	POA
TT34-LCRR	75X33MM TIMER, 24 V, 2 X RELAY	POA	POA
TC34-FCRR	75X33MM COUNTER, 12V, 2 X RELAY	POA	POA
TC34-HCRR	75X33MM COUNTER, 100-230 V, 2 X RELAY	POA	POA
TC34-LCRR	75X33MM COUNTER, 24 V, 2 X RELAY	POA	POA
TT49-FCRR	48X48MM, TIMER, 12V, 2 X RELAY	POA	POA
TT49-HCRR	48X48MM, TIMER, 100-230 V, 2 X RELAY	POA	POA
TT49-LCRR	48X48MM, TIMER, 24V, 2 X RELAY	POA	POA
TC49-FCRR	48X48MM, COUNTER, 12V, 2 X RELAY	POA	POA
TC49-HCRR	48X48MM, COUNTER, 100-230 V, 2 X RELAY	POA	POA
TC49-LCRR	48X48MM, COUNTER, 24 V, 2 X RELAY	POA	POA
-B	INTERNAL BATTERY		
	ADD B TO PART NUMBER ONLY ON COUNTER	POA	POA

