

TLZ 11 digital thermostats (-100 to +500°C)

The TLZ11 is a range of digital thermostats giving basic on/off control. Ptc or ntc input only, these units can have one or two relay outputs along with a volt free (digital input) contact. In addition to the outputs the TLZ can also have a buzzer for over or under temperature alarms.



FEATURES

IP65 FRONT FACIA
°C OR °F SELECTABLE
-100 + 500/ 0-300°C HI TEMP
-50 + 150 STD
0.1°C RESOLUTION

SPECIFICATION

DISPLAY: 4 digit led (red)
OPERATING TEMP: -10 to +55°C
DIMENSIONS: 33mm x 75mm x 64mm
POWER SUPPLY: 100-230 vac, 12 vac/dc, 24 vac/dc
OUTPUTS: up to 2 x relay, 1 x 16 amp, 1 x 8 amp
ACCURACY: 0.5% full scale

PART CODES	DESCRIPTION	PRICE (£)	
		1 - 9	10 +
TLZ11-FS	12V AC/DC in, 16 Amp Relay out	POA	POA
TLZ11-FSR	12V AC/DC in, 1 x 16 Amp, 1 x 8 Amp out	POA	POA0
TLZ11-LS	24V AC/DC in, 16 Amp Relay out	POA	POA
TLZ11-LSR	24V AC/DC in, 1 x 16 Amp, 1 x 8 Amp out	POA	POA
TLZ11-HS	100-230V AC in, 1 x 16 Amp Relay out	POA	POA
TLZ11-HSR	100-230V AC in, 1 x 16 Amp, 1 x 8 Amp out	POA	POA
TLZ11-HSRB	100-230V AC in, 1 x 16 Amp, 1 x 8 Amp out + buzzer	POA	POA
TLZ11-HS----P-HI TEMP	100-230V AC in, 1 x 16 amp out, (-100 to +500°C range)	POA	POA
TLZ11-HSR---P-HI TEMP	100-230V AC in, 1x16 amp, 1 x 8 amp, (-100 to +500°C range)	POA	POA
TLZ35-HS	100-230V PTC in, 1 x Relay out, Din Rail Mount	POA	POA
TLZ35-HRS	100-230V PTC in, 2 x Relay out, Din Rail Mount	POA	POA

See page 4 for sensors for TLZ instruments

PRODUCTS ALSO AVAILABLE

This wall mounted thermostat incorporates our TLZ11 digital thermostat in a strong weather resistant polycarbonate enclosure. The unit has three cable entries for supply in, sensor input and switched line (16 amp relay). Please contact the sales office for further information.

